



SPAR 5 EX AND 5 AXE



PRODUCT FEATURES

- The **SPAR 5 EX** and **5 AXE** are made of Polyspar and can replace rollers of **all sizes**.
- Its Polyspar ensures **optimum sliding without belt wear**.
- Recommended for material sizes of **1-1/4" or less**.
- Belt speed must be **less than 450 fpm**.
- Material dropping height must be **less than 36"**.

The **SPAR 5 EX** and **5 AXE** are made for unsafe areas such as transfer points.

Troughing configuration must conform to belt manufacturer recommendations.

Thanks to its good sliding properties, the **SPAR 5 EX** and **5 AXE** will **not wear the belt if the belt is clean**.

For **larger material sizes or material falling from a height greater than 1m**, the **SPARET** or the **SPARMAT** are recommended.



GLINDING IDLER

- The **SPAR 5 EX** and **5 AXE** are installed in the place of a roller, thus **eliminating** the nip point and the **risk of nip point accidents**.
- Made of Polyspar and designed to **replace roller**, thanks to their adjustable brackets. **No other changes** to your belt installation are necessary.



R. BRUNONE

CONTAINMENT • OPTIMISATION • SAFETY OF CONVEYORS

1, rue de la Cressonnière
27950 Saint-Marcel, France
Tél.: +33 (0)2 32 64 20 20
E-mail: commercial@brunone-innovation.fr